



182T-184T



56HC w/Feet



56 Foot mount

- Heavy steel fan guard
- Epoxy powder coat paint finish
- Torq® centrifugal & stationary switches
- Upgraded gasketing
- Precision balanced rotor

\* = Premium Efficiency    Δ = Cap start-cap run    ≤5/8" shaft    ≥7/8" shaft    56H=56/140 dual base

HP	RPM	FRAME	IND#	VOLTAGE	230V FLA	OVER LOAD	WGT LB	"C" DIM.	LIST	
.33	1800	56	C256	115/208-230	2.9	MAN.	24	10.81	292	
		56C no feet	C290						306	
		56C/Feet	C256C						306	
.50	1800	56	C086	115-208-230	3.9	MAN.	25	10.81	317	
		56C no feet	C492						331	
		56C/Feet	C086C						331	
.75	1800	56	C087	115-208-230	5.0	MAN.	30	11.25	350	
		56C no feet	C493						364	
		56C/Feet	C087C						364	
		56	Δ* K087		3.6		36	12.4	375	
		56C/Feet	Δ* K087C						375	
1.0	3600	56	C142	115-208-230	5.9	MAN.	32	11.3	376	
		56C/Feet	C142C						390	
	1800	56	Δ* K088		4.4		MAN.	39	12.8	395
		56C no feet	Δ* K494							409
		56C/Feet	Δ* K088C							409
1150	56H	Δ* K401	115/230	5.9	NONE	49	13.5	550		
1.5	3600	56	C109	115/208-230	8.1	MAN.	36	11.9	413	
		56C/Feet	C109C						427	
	1800	56H	K089		9.0		MAN.	43	13.31	452
		56C no feet	K495							466
		56HC/Feet	K089C							466
2.0	3600	56H	C402	115-208-230	10.0	MAN.	44	13.3	491	
		56H	C402C						505	
	1800	56HZ	Δ*> K090	230	9.5		MAN.	48	14.25	524
		56HC/Feet	Δ*< K090Z							538
		56HCZ/Feet	Δ*> K090F							538
3.0	3600	145T	K341	230	12.5	NONE	53	13.6	583	
		145TC/Feet	K341C						597	
	1800	184T	Δ* K003	208-230	16.0	MAN.	90	17.7	795	
		184T	Δ* K003C						865	
5.0	1800	184T	Δ* K005	208-230	23.0	MAN.	100	17.5	920	
		184T	Δ* K005C				100	17.5	990	
C FLANGE		56	56-FLANGE	Fits only 56 and 56H frame motors in this table					40	
C FLANGE		56HZ/140T	140-FLANGE	Fits only 56HZ and 140T frame motors in this table					40	
C FLANGE		184T	180-FLANGE	Fits only 184T frame 1 phase motors in this table					50	