



TECO AC FREQUENCY DRIVES



L510 Compact, low cost, versatile, easy to program, ideal for OEM's.

L510 1 Phase	HP	Volts	LIST
L510-1P2-H1-UE	0.25	115V	355.00
L510-1P5-H1-UE	0.5	115V	344.00
L510-101-H1-UE	1	115V	371.00
L510-2P2-H1-UE	0.25	230V	316.00
L510-2P5-H1-UE	0.5	230V	322.00
L510-201-H1-UE	1	230V	339.00
L510-202-H1-UE	2	230V	466.00
L510-203-H1-UE	3	230V	599.00
3 Phase Only	HP	Volts	LIST
L510-2P5-H3-UE	0.5	230V	332.00
L510-201-H3-UE	1	230V	339.00
L510-202-H3-UE	2	230V	459.00
L510-203-H3-UE	3	230V	511.00
L510-401-H3-UE	1	460V	471.00
L510-402-H3-UE	2	460V	518.00
L510-403-H3-UE	3	460V	626.00

A510 Control for today's demanding motor driven applications.

A510 - Single and 3 Phase			
	HP	Volts	LIST
A510-2001-C3-UE	1	230V	745.00
A510-2002-C3-UE	2	230V	781.00
A510-2003-C3-UE	3	230V	961.00
A510- 3 Phase Only			
A510-2005-C3-UE	5	230V	1,009.00
A510-2008-C3-UE	7.5	230V	1,465.00
A510-2010-C3-UE	10	230V	1,586.00
A510-2015-C3-UE	15	230V	2,101.00
A510-2020-C3-UE	20	230V	2,461.00
A510-2025-C3-UE	25	230V	3,038.00
A510-4001-C3-UE	1	460V	769.00
A510-4002-C3-UE	2	460V	805.00
A510-4003-C3-UE	3	460V	973.00
A510-4005-C3-UE	5	460V	1,081.00
A510-4008-C3-UE	7.5	460V	1,573.00
A510-4010-C3-UE	10	460V	1,688.00
A510-4015-C3-UE	15	460V	2,161.00

Accessories available: Line/Load Reactors, dV/dT Filters, Braking Resistors, Sine Wave Filters, Matrix Filters



L510



A510

L510 MEDIUM DUTY ADVANCED MICRO DRIVE - Chassis (IP20)

- .25 to 1 HP, 115V, 1 Phase in, 0-230V, 3 Phase out, 50/60Hz
- .25 to 3 HP, 230V, 1 Phase in, 0-230V, 3 Phase out, 50/60Hz
- .50 to 3 HP, 230V, 3 Phase in, 0-230V, 3 Phase out, 50/60Hz
- 1 to 3 HP, 460V, 3 Phase in, 0-460V, 3 Phase out, 50/60Hz
- Sensorless Vector or V/Hz with Auto Torque Boost Feature
- Extensive Diagnostic and Monitoring Capabilities
- Din Rail Option
- PID Control
- 8 Preset Speeds
- Two Multi-Function Analog Inputs/ One Analog Output
- Built-in Modbus or BACnet Protocol via RJ 45 Interface

A510 HEAVY DUTY AC DRIVE - NEMA 1

- 1 to 100 HP (CT), 1 to 125 HP (VT), 230V, 50/60Hz, 3 Phase
- 1 to 200 HP (CT), 1 to 250 HP (VT), 460V, 50/60Hz, 3 Phase
- 1 to 10 HP (CT/VT) 575V, 50/60Hz, 3 Phase
- 15 to 250 HP (CT), 15 to 270 HP (VT) 690V, 50/60Hz, 3 Phase
- Control modes for V/F, V/F w/ PG feedback, Sensorless Vector & Closed Loop Vector
- Simple PLC Function Built-in
- Advanced Regenerative Load Handling Capability
- Conformal Coating on PC Boards
- Remotely Mountable LCD Keypad

A510- 3 Phase	HP	Volts	LIST
A510-4020-C3-UE	20	460V	2,581.00
A510-4025-C3-UE	25	460V	3,218.00
A510-5001-C3-UE	1	575V	1,176.00
A510-5002-C3-UE	2	575V	1,275.00
A510-5003-C3-UE	3	575V	1,356.00
A510-5005-C3-UE	5	575V	1,435.00
A510-5008-C3-UE	7.5	575V	1,515.00
A510-5010-C3-UE	10	575V	1,594.00
A510-6020-C3-UE	15	575V	2,591.00
A510-6025-C3-UE	20	575V	3,328.00
A510-6030-C3-UE	25	575V	3,468.00
A510-6015-C3-UE	15	690V	2,312.00
A510-6020-C3-UE	20	690V	2,591.00
A510-6025-C3-UE	25	690V	3,328.00