


GENERAL PURPOSE IP23 COUPLER BRAKES

- Mounts between motor and driven load
- Rugged cast iron & aluminum construction
- Designed to be “C face” connected at both ends
- 6 ft/lb brake can be used with either 56 or 140TC mount (adapter supplied with brake)
- IP23 construction suitable for indoor use
- **Note:** Not suited for overhung loads applied to the output shaft



IND No. 115/208-230V Single Phase	IND No. 208-230/460V Three Phase	IND No. 575V Three Phase	Brake Rating (ft/lbs)	Max HP @ 1725 RPM	Mounts to NEMA Frame	Brake Output Shaft and C Face	Add to Motor “C” Dim	LIST
105671105PF	105671105QF	105671105NF	3	1/2	56C	.625”/56C	5.0”	527
105672105PF	105672105QF	105672105NF	6	1	56C	.625”/56C	5.0”	596
105673107*PF	105673107*QF	105673107*NF	10	2	56C/140TC	.875”/140TC*	5.0”	702
108772101PG	108772101QG	107772101NG	15	3	180TC	1.125”/180TC	8.38”	6315
108773101PG	108773101QG	108773101NG	25	5	180TC	1.125/180TC	8.38”	6452

* Change “07” in IND. No to “05” for 5/8” input/output

Stearns Coupler Brakes also available in IP 55 washdown (Type 4X BISSC Certified)
Call for pricing and availability.

56,000 SERIES: SOLENOID ACTUATED BRAKES

For industrial applications requiring high performance in a compact light-weight package.

- Mounts on 56C face with 5/8” shaft
- Spring-set electrically released
- Adjustable torque, down to 50% of rated nameplate torque
- Manual wear adjustment
- Airgap adjust gage
- Splined hub
- Universal mounting through 15 lb-ft.




AG-I IND No.	VOLTS	LB-FT	LIST
ST 1-056-011-00-BNF	575V.	3	349
ST 1-056-011-00-BQF	230/460V.	3	349
ST 1-056-011-00-BPF	115/230V.	3	349
ST 1-056-021-00-BNF	575V.	6	399
ST 1-056-021-00-BQF	230/460V.	6	399
ST 1-056-021-00-BPF	115/230V.	6	399



TENV Integrated
Brakemotors
on page 4

