

**FEATURES**

- 2 hole "56N" flange (6-3/8" centre)
- Manual thermal protector
- Wrench extension (7/16 in.) on rear shaft
- "Legacy" heavy duty design & durable steel fan guard
- Overspeed protection for centrifugal switch
- Epoxy powder coat paint – upgraded gasketing



C292 1/2 HP

\*K294 1.0 HP

HP	RPM	FRAME	VOLTAGE	IND#	SHAFT"	230V FLA	OVERLOAD	WGT LB	"C" DIM.	LIST
.33	1800	56NY	115/208-230	<b>C291</b>	.5 x 1.5 (w/Flat)	2.9	MAN.	25	11.3	325
.50	1800	56NY	115/208-230	<b>C292</b>	.5 x 1.5 (w/flat)	3.9	MAN.	26	11.3	350
.75	1800	56NY	115/208-230	<b>C293</b>	.5 x 1.5 (w/flat)	5.0	MAN.	30	11.9	390
1.0	1800	56NY	115/208-230	<b>*K294</b>	.625 X 2.0 (w/key)	4.4	MAN.	39	13.1	459
1.5	1800	56NY	115/208-230	<b>K295</b>	.625 X 2.0 (w/key)	9.0	MAN.	43	13.5	500

\* = Premium Efficiency

**BELTED FAN - PREMIUM EFFICIENCY - 48 FRAME**

**FEATURES**

- High Efficiency split start / cap run
- NEMA 48, Resilient base
- Precision balanced rotor
- Very quiet, smooth operation
- Design B *starting* torque for all fan loads

*Vent-Plus*\*



B602, B405



OB033

HP	RPM	FRAME	VOLTAGE	IND#	115V FLA	OVERLOAD	FL EFF %	WGT LB	"C" DIM.	LIST
.25	1800	48	115	<b>B602</b>	2.5	AUTO	71.0	18	9.88	263
.33	1800	48	115	<b>B405</b>	3.2	AUTO	75.0	19	9.88	276
.50	1800	48	115	<b>Δ B585</b>	4.6	AUTO	76.0	24	10.50	333

Δ = Cap start-cap run

**OIL BURNER MOTOR**

**NEW!**

NOTE: STANDARD ROTATION CW FACING LEAD END. (Not reversible)

.33	3450	56N	115	<b>OB033</b>	4.2	MAN.	66.0	14.5	8.6	255
-----	------	-----	-----	--------------	-----	------	------	------	-----	-----

**INSTANT REVERSING - 56 FRAME - ODP**

**FEATURES**

- 115V Permanent Split Capacitor
- Switchless
- Resilient base
- Manual reset overload protection
- Capable of frequent stop/start/reverse

*Premium low-amp replacement for parking gates, sliding gates and overhead doors.*

Δ = 60 minute duty



HP	RPM	FRAME	VOLTAGE	IND#	115V FLA	OVERLOAD	WGT LB	MOUNTING	"C" DIMENSION (IN.)	LIST
.33	1725	S56	115	<b>R231</b>	4.6	MAN.	18	R	10.31	279
.50	1725	S56	115	<b>Δ R241</b>	5.8	MAN.	20	R	10.31	330